

PRODUCT DATASHEET


New original
Industrial control products

+86 755 81481609

sales@kwoco-plc.com

www.kwoco-plc.com

MELSEC-F Series FX3S Main Units and Configuration



FX3S - Keeping it Simple

Controllable I/O: 10 - 30 points

Main Unit I/O: 10/14/20/30 points

- Integrated power supply (AC powered)
- Maintenance-free EEPROM memory, batteryless
- Built-in USB port for the programming communication function to enable high-speed communication at 12Mbps
- Built-in positioning control
- Integrated real-time clock
- Up to 30 I/O

Product Details

All-in-one CPU, power supply and I/O. Expansion options includes adapter and expansion boards for communication, analog control, or temperature input.

Fast Instruction Times

Basic Instructions: 0.21µs / instruction (Contact Instruction)

Applied Instructions: 0.5µs / instruction (MOV Instruction)

Large Memory

4,000 steps of built-in program memory. No battery, no maintenance.

Large Device Memory

Auxiliary Relays: 1,536 points

Timers: 138 points

Counters: 88 points

Data Registers: 3,000 points

FX^{3S}

Expansion Boards




FX3G-232-BD

Communication
FX3G-232-BD
FX3G-422-BD
FX3G-485-BD
FX3G-485-BD-RJ


Analog
FX3G-2AD-BD
FX3G-1DA-BD

Analog Setpoint
FX3G-8AV-BD


Digital I/O
FX3G-4EX-BD
FX3G-2EYT-BD



Special Adapters



FX3U-4AD-ADP



FX3U-4AD-PNK-ADP

Analog
FX3U-4AD-ADP
FX3U-4DA-ADP
FX3U-3A-ADP

Temperature
FX3U-4AD-PT-ADP
FX3U-4AD-TC-ADP
FX3U-4AD-PTW-ADP
FX3U-4AD-PNK-ADP




FX3U-232ADP-MB




FX3U-485ADP-MB

Communication
FX3U-232ADP-MB
FX3U-485ADP-MB
FX3U-ENET-ADP



Interface Converter
FX3S-CNVP-ADP

FX3s Main Units




FX3S-10MR/ES

FX3s Main Units 10-30 I/O

FX3S-10MR/ES	AC	D	R	FX3S-20MR/ES	AC	D	R
FX3S-10MT/ES	AC	D	T1	FX3S-20MT/ES	AC	D	T1
FX3S-10MT/ESS	AC	D	T2	FX3S-20MT/ESS	AC	D	T2
FX3S-10MR/DS	DC	D	R	FX3S-20MR/DS	DC	D	R
FX3S-10MT/DS	DC	D	T1	FX3S-20MT/DS	DC	D	T1
FX3S-10MT/DSS	DC	D	T2	FX3S-20MT/DSS	DC	D	T2
FX3S-14MR/ES	AC	D	R	FX3S-30MR/ES	AC	D	R
FX3S-14MT/ES	AC	D	T1	FX3S-30MT/ES	AC	D	T1
FX3S-14MT/ESS	AC	D	T2	FX3S-30MT/ESS	AC	D	T2
FX3S-14MR/DS	DC	D	R	FX3S-30MR/DS	DC	D	R
FX3S-14MT/DS	DC	D	T1	FX3S-30MT/DS	DC	D	T1
FX3S-14MT/DSS	DC	D	T2	FX3S-30MT/DSS	DC	D	T2
				FX3S-30MR/ES-2AD	AC	D	R
				FX3S-30MT/ES-2AD	AC	D	T1
				FX3S-30MT/ESS-2AD	AC	D	T2

AC: AC Power Supply
DC: DC Power Supply
D: DC Input (sink/source)
R: Relay Output
T1: Transistor (sink)
T2: Transistor (source)

Optional Equipment and Software



GOT
GOT2000

Interface Converter
FX-232AWC-H

Software
GX Works2
GX Works2 FX

Accessories

Memory Cassette



FX3G-EEPROM-32L

Display Module



FX3S-5DM

FX3S

FX3S Main Units with 10 - 14 I/O

Model Number	FX3S-10MR/DS	FX3S-10MR/ES	FX3S-10MT/DS	FX3S-10MT/DSS	FX3S-10MT/ES	FX3S-10MT/ESS
Stocked Item	S	S	S	S	S	S
Certification	UL • cUL • CE (EMC)					
Integrated Inputs/Outputs	10	10	10	10	10	10
Power Supply (V)	24VDC	100 - 240VAC	24VDC	24VDC	100 - 240VAC	100 - 240VAC
Integrated Inputs	6	6	6	6	6	6
Integrated Outputs	4	4	4	4	4	4
Output Type	Relay	Relay	Transistor (Sink)	Transistor (Source)	Transistor (Sink)	Transistor (Source)
Power Consumption (W)	6	19	6	6	19	19
Weight (kg)	0.22	0.3	0.22	0.22	0.3	0.3
Dimensions (W x H x D) mm	60 x 90 x 75	60 x 90 x 75	60 x 90 x 49	60 x 90 x 49	60 x 90 x 75	60 x 90 x 75

FX3S Main Units with 10 - 14 I/O

Model Number	FX3S-14MR/DS	FX3S-14MR/ES	FX3S-14MT/DS	FX3S-30MT/DSS	FX3S-14MT/ES	FX3S-14MT/ESS
Stocked Item	S	S	-	S	S	S
Certification	UL • cUL • CE (EMC)					
Integrated Inputs/Outputs	10	14	14	14	14	14
Power Supply (V)	24VDC	100 - 240VAC	24VDC	24VDC	100 - 240VAC	100 - 240VAC
Integrated Inputs	8	8	8	8	8	8
Integrated Outputs	6	6	6	6	6	6
Output Type	Relay	Relay	Transistor (Sink)	Transistor (Source)	Transistor (Sink)	Transistor (Source)
Power Consumption (W)	6.5	19	6.5	6.5	19	19
Weight (kg)	0.22	0.3	0.22	0.22	0.3	0.3
Dimensions (W x H x D) mm	60 x 90 x 49	60 x 90 x 75	60 x 90 x 49	60 x 90 x 49	60 x 90 x 75	60 x 90 x 75

FX3S Main Units with 20 - 30 I/O

Model Number	FX3S-20MR/DS	FX3S-20MR/ES	FX3S-20MT/DS	FX3S-20MT/DSS	FX3S-20MT/ES	FX3S-20MT/ESS
Stocked Item	S	S	-	S	S	S
Certification	UL • cUL • CE (EMC)					
Integrated Inputs/Outputs	20	20	20	20	20	20
Power Supply (V)	24VDC	100 - 240VAC	24VDC	24VDC	100 - 240VAC	100 - 240VAC
Integrated Inputs	12	12	12	12	12	12
Integrated Outputs	8	8	8	8	8	8
Output Type	Relay	Relay	Transistor (Sink)	Transistor (Source)	Transistor (Sink)	Transistor (Source)
Power Consumption (W)	7	20	7	7	20	20
Weight (kg)	0.3	0.4	0.3	0.3	0.4	0.4
Dimensions (W x H x D) mm	75 x 90 x 49	75 x 90 x 75	75 x 90 x 49	75 x 90 x 49	75 x 90 x 75	75 x 90 x 75

FX3S Main Units with 20 - 30 I/O

Model Number	FX3S-30MR/DS	FX3S-30MR/ES	FX3S-30MT/DS	FX3S-30MT/DSS	FX3S-30MT/ES	FX3S-30MT/ESS
Stocked Item	S	S	-	S	S	S
Certification	UL • cUL • CE (EMC)					
Integrated Inputs/Outputs	30	30	30	30	30	30
Power Supply (V)	24VDC	100 - 240VAC	24VDC	24VDC	100 - 240VAC	100 - 240VAC
Integrated Inputs	16	16	16	16	16	16
Integrated Outputs	14	14	14	14	14	14
Output Type	Relay	Relay	Transistor (Sink)	Transistor (Source)	Transistor (Sink)	Transistor (Source)
Power Consumption (W)	8.5	21	8.5	8.5	21	21
Weight (kg)	0.35	0.45	0.35	0.35	0.45	0.45
Dimensions (W x H x D) mm	100 x 90 x 49	100 x 90 x 75	100 x 90 x 49	100 x 90 x 49	100 x 90 x 75	100 x 90 x 75

FX3S Main Units with 30 I/O and Analog Inputs

Model Number	FX3S-30MR/ES-2AD	FX3S-30MT/ES-2AD	FX3S-30MT/ESS-2AD
Stocked Item	S	S	S
Certification	UL • cUL • CE (EMC)		
Integrated Inputs/Outputs	30	30	30
Power Supply (V)	100 - 240VAC	100 - 240VAC	100 - 240VAC
Integrated Digital Inputs	16	16	16
Integrated Analog Inputs	2 (10 bit, 0-10VDC)	2 (10 bit, 0-0VDC)	2 (10 bit, 0-10VDC)
Integrated Outputs	14	14	14
Output Type	Relay	Transistor (Sink)	Transistor (Source)
Power Consumption (W)	21	21	21
Weight (kg)	0.45	0.45	0.45
Dimensions (W x H x D) mm	100 x 90 x 49	100 x 90 x 75	100 x 90 x 75



2025 KWOCO CONTACT

WHY CHOOSE KWOCO

- Extensive inventory
- Brand new, Original products

CONTACT BY

Email: sales@kwoco-plc.com

Web: www.kwoco-plc.com

Tel: +86-755-81481609

